

SJ9253RT | Scissor Lift

Working height

18.15m

Closed length	4.42m
Closed height	3.19m
Stowed height (guardrails lowered)	2.40m
Closed width	2.30m
Platform size	4.36m x 1.82m
Platform length (deck extended)	5.88m
Max SWL	680kg
Weight	8215kg


Alternative machines

GS53
9250
9250X
H18SX

Manufacturer

Skyjack

Working envelope



18.2m

Standard features



Optional extras



0345 745 0000

nationwideplatforms.co.uk

**Nationwide
Platforms**
A **LOXAM** Company

Understanding this Product Specification Sheet

This product specification sheet is designed to help you better understand the capabilities and key features of the piece of equipment and whether it will meet your requirements.

The working envelope with height/reach indicator provides a quick visual reference to assist your equipment selection.

If you are unsure about any aspect of this piece of equipment, or would like more information to assist with your selection, please call our expertly trained staff on **0345 745 0000**

Height and outreach

Working height Horizontal outreach

AMWP11.5-8100
Boom Lift

Working height	11.2m	Alternative machines
Horizontal outreach	3m	Star10
Closest length	2.55m	Star10A
Closest height	1.95m	Manufacturer
Closest width	1m	Driftl
Rotation	345°	
Platform height	0.2m	
Max SWL	200kg	
Weight	2000kg	
Deck size	0.62m x 0.87m	

Working envelope

Standard features

-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-

Optional extras

-
-
-
-
-
-
-
-
-
-
-
-
-
-
-
-

0345 745 0000
nationwideplatforms.co.uk
 Nationwide Platforms
A BREXIT COMPANY

Standard features

- Battery power
- Diesel power
- Lithium battery
- Hybrid power
- Dual fuel option
- Gas power option
- Rough terrain (2 wheel drive)
- Rough terrain (4 wheel drive)
- IPAF licence type
- IPAF licence type
- IPAF licence type
- IPAF licence type
- IPAF licence type
- Tracked
- Mast boom
- Articulating boom
- Straight telescopic boom
- Non-marking tyres
- Outrigger legs
- Maximum people in cage*
- Push around vehicles
- Operator powered
- Indoor use only
- Indoor/Outdoor
- Self drive
- J1B rotation
- IPAF driving licence type
- Power to platform
- Generator

Optional extras

- SkySiren®
- SkySiren® PCS
- SkySentry®
- SkyRak®
- SkyRakPlus®
- SkyRakBoom®
- SkyRakMulti™
- SkyTel™
- SkyRakEdge™
- SkyShield™
- SkyScreen™
- Material handling attachments
- Generator
- Camera pod
- Circular camera cage
- Wendy lighting frame

*The number refers to indoor or outdoor uses. Call us for details.

Please note that all technical information referred to in this document is intended for guidance purposes only and does not act as a replacement for the manufacturer's specification or equipment user guides which should be referred to prior to placing your order. No responsibility can be accepted in the event that this document contains any errors, omissions or data that is different from that in the manufacturer's specification or equipment user guides.